DATASHEET

The Ambu[®] Reusable PEEP 10 & 20 valves are designed to provide PEEP when used in conjunction with manual resuscitators, ventilators, anaesthesia machines and CPAP systems. Both Ambu[®] Reusable PEEP valves are available in two sizes based on the size of the connector; a 30 mm connector or a 22 mm connector. The Ambu[®] Reusable PEEP valves are designated as MR Unsafe.

The Ambu[®] Reusable PEEP 10 Valve is adjustable, meaning it can be used to provide PEEP ranging between 0 - 10 cmH₂O. The Ambu[®] Reusable PEEP 20 Valve can also be adjusted to provide PEEP ranging between 1.5 - 20 cmH₂O. Being completely adjustable allows for the Ambu[®] Reusable PEEP Valves to be used to apply a specific amount of PEEP to suit patient requirements.

After use, the Ambu® Resusable PEEP Valves are suitable for both manual and automated cleaning, disinfection and sterilisation. They are also capable of being sterilised at a temperature of 134 °C, and can be reprocessed up to 30 times.

Ambu[®] Reusable PEEP 10 & 20 Valves



KEY BENEFITS

Ambu[®] Reusable PEEP Valves are adjustable to allow for varying levels of PEEP to be applied. The Reusable PEEP 10 Valve can be adjusted to provide between 0 - 10 cmH₂O of PEEP. The Reusable PEEP 20 Valve can be adjusted to provide between 1.5 - 20 cmH₂O of PEEP.

Both available in two different sizes; one with a 30 mm connector and another with a 22 mm connector, to allow for connection to various devices.

Suitable for reprocessing up to 30 times.

Capable of being resterilised at a temperature of 134 °C.



ORDERING SPECIFICATIONS

ltem no.	Description
A137 001 000	PEEP 10 with inlet ID 30 mm and OD 22 mm
A000 137 000	PEEP 10 with inlet ID 30 mm
A000 138 000	PEEP 10 with inlet OD 22 mm
A000 213 000	PEEP 20 with inlet ID 30 mm
A000 177 000	PEEP 20 with inlet OD 22 mm

MATERIALS

Product	Material
Transparent plastic parts	Polysulphone
Plastic parts of valve body	Polysulphone with delrin disc and silicone oil
Adjustment cap	Polyamide (nylon)
Sealing in adjustment cap	EPDM rubber
Springs	Stainless steel

SIZE

Dimension	
Length	Ø 65 - 78 mm (depending on adjustment, diameter 45 mm)
Weight	< 45 g



Ambu[®] Reusable PEEP 20 Valve



Ambu[®] Reusable PEEP 10 Valve



Ambu A/S

Baltorpbakken 13 2750 Ballerup Denmark T +45 72 25 20 00 ambu.com

