KEY BENEFITS

Dedicated BAL sampling solution

Simple to operate without assistance

Closed-loop system helps reduce risk of contamination and sample loss

Designed for superior lavage

When it comes to lavage, Ambu leads the way with aScope 5 Broncho Sampler Set, an all-in-one, closed-loop sampling system. This innovative solution is sterile straight from the pack, intuitive to set up and use, and can be operated by a single clinician.

A high degree of control

With aScope 5 Broncho Sampler Set, there is no need to switch tubing during the sampling procedure. The sampler clicks right onto aScope 5 Broncho and allows you to switch between suction and sampling at the turn of a knob. This enables you to operate it without assistance and gives you a high degree of control when navigating the lungs.

Protects the sample from start to finish

Safety comes first with Ambu's sampling solution. Due to its tubeless, integrated system, the Sampler Set reduces the risk of sample loss, contamination, and minimizes sample exposure to the clinicians. The result? Increased safety and sample quality for you, your team, and your patients.

Ambu® aScope™ 5 Broncho 4.2/2.2 Sampler Set The unique, integrated sampling solution





LBL-009100 - V02 - 2023/06. TCC 11512 - Ambu A/S. Technical data may be modified without further notice.

SPECIFICATIONS

| Optical system | | |
|--|----------------------------|--|
| Field of view | 120° | |
| Direction of view | 0° (forward viewing) | |
| Depth of field | 3 - 100 mm | |
| Illumination method | LED | |
| Camera sensor module | CMOS | |
| Insertion portion | | |
| Bending section | 210° up, 210° down | |
| Insertion cord diameter | 4.2 mm (0.17") | |
| Distal tip diameter | 4.4 mm (0.17") | |
| Maximum diameter of insertion portion | Max Ø 4.8 mm (0.19") | |
| Minimum endotracheal tube size (inner diameter) | 5.0 mm/15 Fr | |
| Working length | 600 mm (23.6") | |
| Rotary function | 120° left/right | |
| Depth marks | Every 5 cm | |
| Working channel | | |
| Instrument channel width | 2.2 mm (0.09") | |
| Minimum instrument channel width* | Min. Ø 2. 2 mm (0.09") | |
| Suction connector | | |
| Connecting tube inner diameter | Ø 5.5 - 9.0 m | |
| Sample container | | |
| Sample container volume | 60 ml | |
| Operating environment, storage, and transportation | | |
| Temperature - transportation | -10 - 55 °C (14 to 131 °F) | |
| Temperature - operating environment | 10 - 40 °C (50 to 104 °F) | |
| Temperature - storage | 10 - 25 °C (50 to 77 °F) | |
| Relative humidity - storage | 10 - 85 % | |
| Atmospheric pressure - storage | 50 - 106 kPa | |
| Sterilisation | | |
| Method of sterilisation | ETO | |
| Other | | |
| Compatibility | Cryobiopsy probes | |
| Latex and phthalate free | Yes | |
| Edical and printing free | 100 | |



| Item no. | Product name | Quantity |
|-----------|---|----------|
| 620002000 | aScope™ 5 Broncho 4.2/2.2 Sampler Set | 5 |
| 480500000 | aScope BronchoSampler™ 60 SC, sample container spares | 10 |

^{*} There is no guarantee that accessories selected solely using this minimum instrument channel width will be compatible in combination.



Easily attach and detach the sampler from the bronchoscope



Switch between suctioning and sampling at the turn of a knob



Once finished, the retrieved sample is sealed, protected and ready to go



■ Ambu A/S

Baltorpbakken 13 2750 Ballerup Denmark +45 72 25 20 00 ambu.com

