

Ambu® WhiteSensor 0715M

ECG Electrode - Single use



Key Benefits

- Skin friendly solid gel
- Large size
- Fish tail tab design reducing electrode lift-offs
- Radiolucent
- MR Conditional

Ambu® WhiteSensor 0715M

Large size tab electrode with solid gel for 12-lead ECG. Presented conveniently with 10 pieces to a card. The fish tail tab design reduces electrode lift-offs even if the

adaptor kinks. This electrode is optimal for the Emergency department.



Solid gel



Polymer backing



Radiolucent



MR Conditional

WhiteSensor

Ambu
Ideas that work for life

Specifications

Dimensions	
Electrode size (length x width in mm)	34 x 26
Skin contact size (length x width in mm)	25 x 26
Adhesive area (in mm ²)	650
Height excluding connector (in mm)	0.8
Sensor	
Sensor material	Silver, silver chloride (Ag/AgCl)
Gel system	Chloride based, solid gel
Gel area (in mm ²)	650
Sensor area (in mm ²)	650
Electrical data (ANSI/AAMI)	
AC impedance - typical	250 Ω
DC offset potential - typical	0.2 mV
Defibrillation overload recovery - typical	11 mV
Rate of change for polarisation potential - typical	0.2 mV/s
Combined offset instability and internal noise	0.0 μV
Bias current tolerance (over 4 hours for tabs)	3.2 mV

Environment	
PVC-free electrode	Yes
Electrode not made with natural rubber latex	
PVC-free packaging	Yes
X-Ray & MRI	
Radiolucent	Yes
MR Conditional	Yes**
Shelf life	
Opened pouch	1 month
Sealed pouch	24 months*

*from date of production

Accessories	
Skin Preps	Ref: 2121M
Snap Clips	Ref: 0334M

Materials

Electrode	
Bio-compatible	Yes
Connector	Graphite snap-clip terminal
Upper substrate	Coated paper/polyester/ conducting graphite
Release liner	Siliconised coated paper
Precaution	
Single use only	

Packaging	
Pouch (outer/middle/ inner layers)	Coated paper-polyethylene/aluminium/ ionomer (Surlyn)
Inner carton	Printed cardboard
Shipping carton	Printed corrugated board
Standard Packaging	
Quantity/liner	10
Quantity/pouch	100
Inner carton	500
Shipping carton	5000
Minimum sales	5000

Available configurations

Quantity/pouch	100
	Quantity per inner/outer box
0715M	500/5000

** Static magnetic field of 1.5 Tesla and 3 Tesla only. Maximum spatial gradient field of 25,000 Gauss/cm or 250 Tesla/m. Maximum whole body averaged specific absorption rate (SAR) of 2 W/kg for 15 minutes of scanning.

Ambu A/S
 Baltorpbakken 13
 DK - 2750 Ballerup
 Denmark
 Tel. +45 7225 2000
 Fax +45 7225 2053
 www.ambu.com