

Ambu® WhiteSensor 3552

ECG Electrode - Single use



Key Benefits

- Highly conductive wet gel and strong adhesion for stable and clear tracings
- Offset connector - fitting or tab

Ambu® WhiteSensor 3552

The Ambu WhiteSensor 3552 offset electrode is featuring a combination of wet gel and enhanced adhesion providing stable and clear tracings in ECG resting applications. The offset connector is available with a fitting or as a tab. The occlusive backing of the electrode makes it resistant to fluids.



Wet gel



Foam backing

WhiteSensor

Ambu^{*}
Ideas that work for life

Specifications

Dimensions		
Electrode size (W x L in mm)	52 x 35	
Adhesive area (in mm ²)	1133	
Height excluding connector/wire (in mm)	2.7	
Sensor		
Sensor material	Silver/silver chloride	
Gel system	Wet gel	
Sensor area (in mm ²)	113	
Gel area/measuring area (in mm ²)	201	
Electrical data (ANSI/AAMI)		
AC impedance	≤ 450 Ω	
DC offset voltage	≤ 1 mV	
Defibrillation overload recovery	≤ 10 mV	
Rate of change of polarization potential	≤ 0.5 mV/s	
Impedance after SDR (ACZ)	≤ 300 Ω	
Combined offset instability and internal noise	≤ 100 μV	
Bias current tolerance (over 8 hours)	≤ 100 mV	
Environment		
PVC-free electrode	Yes	
Electrode not made with natural rubber latex		
PVC-free packaging	Yes	
X-Ray & MRI		
	with A-Connector	with Clip Connector
Radiolucent	No	Yes
MR Conditional	No	Yes **
Shelf life		
Opened pouches	1 month	
Unopened pouches	18 months *	

* From date of production

** Static magnetic field of 1.5 Tesla and 3 Tesla only. Maximum spatial gradient field of 12.900 Gauss/cm or 129 Tesla/m. Maximum whole body averaged specific absorption rate (SAR) of 2 W/kg for 15 minutes of scanning.

Connectors



C = Clip



A = 4 mm fitting

Materials

Electrode	
Bio-compatible	Yes
Sponge (Gel Foam)	Polyester Polyurethane Reticulated
Sensor	Silver/silver chloride (Ag/AgCl)
Outer carrier	Polyethylene foam (enhanced)
Outer adhesive	Polyacrylate
Connector	Graphic clip (C) Stainless steel stud (in A-connector)
Fitting	Polypropylene
Liner	PET
Packaging	
Pouch	Polyester/ Aluminum/ Polyethylene
Inner and outer carton	Corrugated box

Standard Packaging	
Quantity/pouch	50, 100
Quantity/box	750/4500, 1500/9000
Minimum sales	750/4500, 1500/9000

Options	
Connectors	C, A
Precaution	
Single use only	

Available configurations

Reference number	Units/card	Units/pouch	Units/inner box	Units/outer box
3552-00-C/100	5	100	1500	9000
3552-00-A/50	5	50	750	4500

Ambu A/S
Baltorpbakken 13
DK - 2750 Ballerup
Denmark
Tel. +45 7225 2000
Fax +45 7225 2053
www.ambu.com

3552-00-X
■ Product
■ Wire length
■ Connector

CE US: Rx only